



OML-75,90,100,110

OPEN MERCHANDISERS

Remote Open Merchandiser

(5 rows shelves + Base)

Standard features

- 5 rows shelves + Base
- Thermostat Electronic Control
- Externally Equalized TXV
- Manual Night Curtain
- Price Tag Holder in Front of Base Tray
- Aluminium Profile Air Return Grills
- Mirrored side wall right/left or Glass Sides
- LED Lights
- Steel Shelves with Front Glass Stoppers
- PVC labelling Profiles
- Dixell thermostat with 2 Probes
- 4000k bar led for top canopy
- 4000k bar led for undershelf lighting
- Wellington ERC2 electronic fan motor
- Multiplexing
- Stainless Steel Wet Surfaces, Fan Sheet and Evaporator Cover
- Epoxy Coated Evaporator
- Stainless Steel Evaporator Box with Heating Element and Evaporator Cover
- Electrostatic Powdered Paint For Both Interior-Exterior (choice of colors Black or White)

Dimensions

Model	OML-75-4	OML-75-6	OML-75-8	OML-75-10	OML-75-12
Length (inches)	49"	74"	98"	120"	148"
Width (inches)	29"	29"	29"	29"	29"
Amperage	2A	2.5A	3.5A	4.5A	5A
Power	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ
BTU/h per foot	1635	1635	1635	1635	1635
Evaporating Temp	-8C	-8C	-8C	-8C	-8C

Model	OML-90-4	OML-90-6	OML-90-8	OML-90-10	OML-90-12
Length (inches)	49"	74"	98"	120"	148"
Width (inches)	35"	35"	35"	35"	35"
Amperage	2A	2.5A	3.5A	4.5A	5A
Power	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ
BTU/h per foot	1690	1690	1690	1690	1690
Evaporating Temp	-8C	-8C	-8C	-8C	-8C

Model	OML-100-4	OML-100-6	OML-100-8	OML-100-10	OML-100-12
Length (inches)	49"	74"	98"	120"	148"
Width (inches)	39"	39"	39"	39"	39"
Amperage	2A	2.5A	3.5A	4.5A	5A
Power	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ
BTU/h per foot	1711	1711	1711	1711	1711
Evaporating Temp	-8C	-8C	-8C	-8C	-8C

Model	OML-110-4	OML-110-6	OML-110-8	OML-110-10	OML-110-12
Length (inches)	49"	74"	98"	120"	148"
Width (inches)	43"	43"	43"	43"	43"
Amperage	2A	2.5A	3.5A	4.5A	5A
Power	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ	115V 60HZ
BTU/h per foot	1745	1745	1745	1745	1745
Evaporating Temp	-8C	-8C	-8C	-8C	-8C

Above mentioned measurement are from internal part of the equipment. Side panel will be extra

* Customizable options available; * Multiple shelves available; * All measurements are approximates; * Specifications are subject to change without notice; * All equipment are designed to operate in a controlled environment below 75°F (+24°C) temperature and HR 55% relative humidity;

